

AMENDMENTS TO THE CLAIMS

A listing of the claims is as follows:

1. (Currently amended) An electrostatic discharge (ESD) NMOSFET with a lower trigger voltage comprising:

a substrate having first, second and third wells formed in said substrate, ~~and separated by shallow-well trench isolation regions structures, and~~ generally separating the bottom of said ~~second~~ first well from said substrate with a segmented conductive band;

a source and drain region in said ~~second~~ first well forming an FET, said drain being connected to an I/O pad for protecting said pad against an ESD event; and

a path of substrate material extending through ~~an a single~~ opening in said ~~segmented~~ conductive band ~~region, increasing the configured to increase~~ substrate resistance in the path ~~of the~~ for current which flows through said I/O pad to ~~a substrate-contact contacts~~ and drain during an ESD event and electrically connecting the ~~second~~ first well to the substrate,

wherein the ~~first~~ second and third wells are completely isolated from the drain, source and ~~substrate-contact contacts by shallow trench isolation structures, and~~

wherein the ~~substrate-contact is~~ contacts are located outside the first, second and third wells and directly connected to the substrate.

2. (Canceled).

3. (Original) An ESD NMOSFET according to claim 1 wherein said ~~first~~ and third wells are N-wells and said conductive band region comprises a semiconductor region which is N doped.

4. (Original) An ESD NMOSFET according to claim 3 wherein said conductive band region is segmented forming said resistive path to said substrate.
5. (Original) The ESD NMOSFET according to claim 1 wherein said FET has a gate connection and source connected to said substrate contact.
6. (Original) The ESD NMOSFET according to claim 1 wherein said drain is connected through a matching impedance to said I/O pad to provide a signal from a circuit on said substrate to said I/O pad.
7. (Currently amended) A method for decreasing the trigger voltage of an ESD NMOSFET comprising:
- locating said ESD NMOSFET in a well of a triple well CMOS structure;
 - connecting said ESD NMOSFET to an I/O pad; and
 - providing a resistive path extending through a single opening in a segmented conductive band from said well to ~~a substrate contact~~ contacts located outside of said triple well and directly connected to a substrate, whereby the trigger voltage of the said ESD NMOSFET is reduced due to said resistive path between said substrate ~~contact~~ contacts and said I/O pad and
- wherein a first, second and third wells are formed in the substrate of the triple well CMOS structure, ~~a first~~
- wherein the second well and third well of the triple well CMOS structure are completely isolated from a drain and source of the ESD NMOSFET by shallow trench isolation structures, and
- wherein the substrate ~~contact~~ contacts ~~is~~ are located outside the first, second and third wells, ~~and~~ completely isolated from the drain and source of the ESD NMOSFET and directly

connected to the substrate.

8. (Original) The method according to claim 7 wherein said resistive path is an opening in said well to form a connection between said NMOSFET and said substrate contact.

9. (Previously presented) The method according to claim 7 wherein said well is a P-well with an N-band of N doped semiconductor material which separates said P-well from said substrate, and which includes an opening forming said resistive path.

10. (Original) The method according to claim 7 wherein said ESD NMOSFET further comprising connecting a gate connection and a source of said NMOSFET to said substrate contact.

11. (Previously presented) The method according to claim 7 wherein a second and third well of said triple well structure are N-Wells, and one of said N-wells is connected to a voltage.

12. (Previously presented) The method according to claim 7 further comprising connecting a gate of said NMOSFET to said substrate contact.

13. (Currently amended) An ESD NMOSFET with a lower trigger voltage comprising:

substrate having first, second and third wells formed in said substrate, said first well comprising a P-well ~~separated from second and third N-Wells by shallow well isolation regions,~~ said first well separated from said substrate along a bottom thereof with a segmented conductive band region;

substrate contacts located outside of said first, second and third wells and the substrate contacts are directly connected to the substrate;

a source and drain region in said ~~P~~Well first well and forming an FET, said drain being connected to an I/O pad for protecting said I/O pad against an ESD event and said drain and source are isolated from second and third N-Wells by shallow trench isolation structures; and

a resistive path extending through ~~an~~ single opening in said segmented conductive band region to said substrate ~~contact~~ contacts, said resistive path decreasing the trigger voltage for said FET.

14. (Currently amended) The ESD NMOSFET according to claim 13 wherein said FET source and gate are connected to said substrate ~~contact~~ contacts.

15. (Currently amended) The ESD NMOSFET according to claim 13 wherein said source is connected to said substrate ~~contact~~ contacts.

16. (New) The ESD NMOSFET according to claim 1 further comprising silicide blocked regions formed over the source and drain.

17. (New) The method for decreasing the trigger voltage of an ESD MOSFET according to claim 7 further comprising silicide blocked regions formed over the source and drain.

18. (New) The ESD NMOSFET according to claim 13 further comprising silicide blocked regions formed over the source and drain.